

DTTW572 – WATERPROOF THIN TIP THERMOMETER



-40 to +572°F/-40 to 300°C

0 18436 00507 0

- NSF® Certified
- 4-second response
- Waterproof (IPX7: protected from water up to 3 feet/1 meter for 30 minutes)
- Field calibration
- High heat
- Max/min mode
- Hold mode
- 180° rotating display
- Big digit
- On/off button
- Auto-off after 10 minutes
- Food-safe ABS plastic with BioCote®
- 304 stainless steel stem
- Temperature guide on thermometer
- 2-way mounting: pocket clip/hook
- 1.5 mm thin tip with 3.5"/8.9 cm stem
- Two LR44 button alkaline batteries included

List price: **36.50**

All-time bestseller! Now shipping

TCTW572 – WATERPROOF FOLDING THERMOCOUPLE THERMOMETER



-58 to +572°F/-50 to +300°C

0 18436 00508 7

- NSF® Certified
- 4-way rotating display
- 3-second response
- Waterproof (IPX7: protected from water up to 3 feet/1 meter for 30 minutes)
- Extra big digit
- Backlit display
- Field calibration
- Automatic on/off
- Food-safe ABS plastic with BioCote®
- 304 stainless steel probe
- Temperature guide on thermometer
- Mounting: loop
- 1.5 mm thin tip with 4.33"/11.0 cm probe
- Two AAA alkaline batteries included

List price: **89.00**

Now shipping

DTL572 – LOLLIPOP THERMOMETER



-40 to +572°F/-40 to 300°C

Yellow	DTL572-Y	0 18436 00511 7
Red	DTL572-R	0 18436 00512 4
Green	DTL572-G	0 18436 00513 1
Blue	DTL572-B	0 18436 00514 8

- NSF® Certified
- 4-second response
- Waterproof (IPX7: protected from water up to 3 feet/1 meter for 30 minutes)
- Field calibration
- High heat
- Max/min mode
- Hold mode
- Big digit
- On/off button
- Auto-off after 10 minutes
- Food-safe ABS plastic with BioCote®
- 304 stainless steel stem
- Temperature guide on sheath
- Mounting: pocket clip
- 1.5 mm thin tip with 4.3"/11.0 cm stem
- Two LR44 button alkaline batteries included

List price: **32.00**

Now shipping

SD0204 – DIGITAL HIGH PRECISION SCALE, 2 LB



2 lb/1 kg by lb:oz/kg.g

0 18436 00839 2

- NSF® Certified
- Precise to 0.01 oz/0.1 g
- Tare function
- Hold mode
- Field calibration
- Selectable units
- Overload indication
- Low battery indication
- Food-safe ABS plastic with BioCote®
- Removable stainless steel platform
- On/off button
- Auto-off after 2 minutes, disabled when the AC adapter is used
- Resolution: 0 lb:0.01 oz, 0.1 g
- Platform Size: 5.35 W x 5.35 L (in)/ 13.6 W x 13.6 L (cm), removable
- Dimensions: 7.87 W x 1.75 H x 5.90 D (in)/ 20.0 W x 4.45 H x 15.0 D (cm)
- Two AAA batteries included
- Power Adapter: 100-240 VAC 50/60Hz input, 9V DC (500mA) output included

List price: **125.00**

Now shipping

SD0202 – DIGITAL HIGH PRECISION SCALE, 2 LB



2.2 lb/1000 g by oz/g

0 18436 00821 7

- Precise to 0.01 oz/0.1 g
- Tare function
- Stainless steel platform
- Selectable units
- Overload indication
- Battery status indication
- Food-safe ABS plastic housing
- On/off button
- Auto-off after 4 minutes
- Resolution: 0.01 oz, 0.1 g
- Platform Size: 4.45 x 4.45 (in)/11.3 x 11.3 (cm)
- Dimensions: 4.45 W x 0.94 H x 7.13 D (in)/11.3 W x 2.4 H x 18.1 D (cm)
- Two AAA carbon zinc batteries (WERCSmart) included

List price: **40.00**

Now shipping

SDC0602 – COFFEE SCALE & TIMER, 6.5 LB



3 kg/6.5 lb/3 L by g/oz/ml; 100 min by min/sec

0 18436 00840 8

- Precise to 0.1 g, 0.005 oz, 0.1 ml
- Tare function
- Counts up
- Backlit digits
- Button feedback beep
- Selectable units
- Overload indication
- Low battery indication
- Polycarbonate polymer housing (heat resistant up to 275°F/135°C)
- On/off button
- Auto-off after 1 minute
- Resolution: 0.1 g, 0.005 oz, 0.1 ml
- Platform Size: 5.1 W x 4.72 L (in)/13 W x 12 L (cm)
- Dimensions: 5.1 W x 0.87 H x 5.9 D (in)/13.0 W x 2.22 H x 15.0 D (cm)
- Built-in rechargeable lithium-ion 3.7V 1000 mAh battery included
- Charging cable included (USB-A to USB-C)

List price: **55.00**

Now shipping